



CN2	
No.	Pin Name
1	VSS
2	VDD
3	V0
4	/WR
5	/RD
6	/CS
7	A0
8	/REST
9	DB0
10	DB1
11	DB2
12	DB3
13	DB4
14	DB5
15	DB6
16	DB7
17	NC
18	VDOUT
19	BLA
20	BLK

Note:

- \*1. LCD Display Type : STN, Negative, Transmissive
- \*2. Viewing Direction : 6H
- \*3. Duty : 1/240; Bias : 1/16
- \*4. Operating Voltage : 5.0V
- \*5. Backlight Type : White LED, 5.0V
- \*6. Operating Temperature : -20°C~70°C
- \*7. Storage Temperature : -30°C~80°C
- \*8. Controller IC : RA8835

CN3	No.	1~4	5	6	7	8	9	10	11	12	13	14	15
	Pin Name	DO~D4	DIS	YD	FR	LP	XCK	VDD	VSS	VEE	V0	FGND	LEDA

CN1	No.	1	2	3	4	5	6	7~14	15	16	17	18	19	20
	Pin Name	VSS	VDD	V0	A0	/WR	/RD	DB0~DB7	/CS	RST	VEE	SEL1	FGND	LEDA

# HOT DISPLAY

Dwg Title		HTM320240A	
Dwg No.		Date	
		2008-3-25	
Scale	Unit	Tol.	
	mm	±0.2	
Drawn	Checked	Approved	
DDU			